


GD-CI-CC4617T

4 MP Mini Bullet IP-Camera 2.8mm ICR IR LED WDR H.265



- Support Dual Power PoE/DC12V
- 3 Axis Gimbal for wall and ceiling mount
- 0 Lux: Integrated LED IR Illuminator viewable distance up to 30m
- H.265, H.264 & MJPEG compression modes
- WDR (Wide Dynamic Range) for extreme backlight situations
- 4 Megapixel IP Camera with Full HD 1080P real time video

ESSENTIAL

- Product Line Essential: high quality, basic features and remarkably many functions for smaller applications

Item Code: GD-CI-CC4617T

EAN CODE: 4260573062102

Specifications GD-CI-CC4617T**Camera**

Image Sensor:	1/3" progressive Scan CMOS
Video Resolution:	2560 x 1440
Sensitivity Colour:	0.01 Lux @ F1.2 (AGC ON)
Sensitivity B/W:	0 Lux LED IR on
Shutter Speed:	1/3 ~ 1/100, 000 sec
Slow Shutter:	Support

Lens

Lens Focal Length:	2.8 mm
Horizontal Viewing Angle:	100°
Iris F-Number:	F2.0
Lens Mount:	M12

Illuminator

Max. IR Distance:	Up to 30 m
Wavelength:	850nm

Video

Col/B&W:	On, Off, Auto, IR-cut filter removable (ICR)
Wide Dynamic Range:	120 dB
Image Enhancement:	BLC, 3D DNR
Day/Night Switch:	Support auto, scheduled
Image settings:	Saturation, brightness, contrast and sharpness adjustable through client software or web browser

Network

Region of Interest:	Support 1 fixed region
Video Compression:	Main Stream: H.265+, H.265, H.264+, H.264 Sub-Stream: H.265, H.264, MJPEG
H.264 code profile:	Baseline Profile / Main Profile / High Profile
Bit Rate:	32Kbps ~ 8Mbps
Network Protocol:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
Frame Rate:	Main Stream 50Hz: 20 fps @ (2560x 1440) , 25fps @ (2304 x 1296, 1920 x 1080, 1280 x 720) 60Hz: 20 fps @ (2560 x 1440) , 30fps @ (2304 x 1296, 1920 x 1080, 1280 x 720) Sub- Stream 50Hz: 25fps @ (640 x 480, 640 x 360, 320 x 240) 60Hz: 30fps @ (640 x 480, 640 x 360, 320 x 240)
Network memory:	NAS(NFS, SMB/CIFS)
Functions:	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, Ip-address filter

I/O Interface

Network Interface:	1x 10, 100 Base T, TX PoE (RJ-45)
--------------------	-----------------------------------

Item Code: GD-CI-CC4617T

EAN CODE: 4260573062102

Intelligent Functions

Event Source:	Video tampering, network disconnected, IP address conflicted
Intrusion Detection:	Motion Detection

Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
Protection Rating:	IP67
Standard:	ONVIF (Profile S, Profile G), ISAPI

Environmental

Operating Temperature:	-40 °C ~ 60 °C (-40 °F ~ 140 °F)
Humidity:	less than 95%, non condensing

Electrical

Supply Voltage:	12 VDC, PoE (IEEE 802.3af)
Power Consumption:	Max. 5 W

Mechanical

Mount:	Pan: 0° to 360°, tilt: 0° to 180°, rotation: 0° to 360°, 3-Axis Adjustment
Dimensions:	172 × 70 × 65 mm (6.77 × 2.75 × 2.56 inch)
Weight:	280 g (0.62 lb)

Accessories:

GD-BR-AJX05