

GD-ML-AC2430HD

61 cm (23.6") LCD/TFT Monitor LED Backlight 16:9



- Displays a full, flat 23.6" (61 cm) diagonal image
- Designed for professional 24/7 usage
- LED Backpanel illumination
- 1 HDMI, 1 VGA Input



ESSENTIAL

- Product Line Essential: high quality, basic features and remarkably many functions for smaller applications

Specifications GD-ML-AC2430HD**Thermal Module**

Viewing Angle: 170° (H) ~ 170° (V)

Monitor

LCD Panel size: 61 cm (23.6") Diagonal AM-TFT LED Backlight

Pixels - Total: 1920 (H) x 1080 (V)

Pixel Pitch: 0.248 mm (H) x 0.248 mm (V)

Aspect Ratio: 16 : 9

Video

Video Standard: PAL, NTSC

Video Inputs: 1x HDMI, 1x VGA, 1x DVI

Brightness: 250 cd, m²

Contrast Ratio: 1,000:1

Number of Colours: 16.7 million

Response Time: 5 ms

General

OSD (On Screen Display): Yes, multi language

Accessories included: Power Adapter and HDMI cable

Approvals

MTBF at 25° C: > 100, 000 hours

Regulation: CE, EAC, FCC, RoHS Compliant

Environmental

Operating Temperature: 0 °C ~ +40 °C

Humidity: less than 90%, non condensing

Electrical

Supply Voltage: 12 VDC, Power Adapter 100 ~ 240 VAC 50, 60Hz included

Power Consumption: Max. 25 W

Mechanical

Vesa Mount: 100 x 100 mm

Dimensions: 445 x 570 x 190 mm (17.5 x 22.40 x 7.5 inch)

Weight: 3900 g (8.6 lb)